



Pro-grade wireless security system
for ultimate protection

Specification Sheet



SpaceControl

Remote key fob for controlling security modes



Learn more
www.inaxsys.com

AJ-Space-W/B

A key fob for controlling security modes. Features a panic button for sending alarms to your inner circle and a security company in case of trouble.

- Authentication to prevent forgery
- Jamming detection and communication channels encryption
- Two-way communication

Calls for help in case of emergency	Activates full or partial alarm modes	Indicates command execution with color blink
-------------------------------------	---------------------------------------	--

Principle of operation

The device controls the security modes and sends an alarm signal to the Central Monitoring Station by pressing the buttons on the key fob.

Features

Authentication prevents replacement of the device and false alarms.

Installation and set up

Ready to operate straight out the box: the battery is already installed, therefore there is no need to disassemble the detector. With one click, it can be connected to the hub in the mobile application.

Tech specs

Classification	Four-button key fob with command delivery indication
Compatibility	Operates with all Ajax hubs , and range extenders , ocBridge Plus , uartBridge
Number of buttons	4
False alarm prevention	Yes, long press or double press (firmware version 5.54.1.0 or higher. Manufacture date from March 19, 2020)
Deactivation of the panic button	Available
Power supply	Battery: CR2032 battery Power supply voltage: 3 V Battery life — up to 5 years

Jeweller radio technology	<p>Communication range with central unit — up to 1,300 m in an open space</p> <p>Two-way communication between devices</p> <p>Operating frequencies — 868.0-868.6 MHz</p> <p>Self-adjusting RF output power — up to 20 mW</p> <p>Block encryption based on AES algorithm</p> <p>Device polling period — 12–300 s</p> <p>Learn more about Jeweller ></p>
Operating temperature range	-25°C to +50°C
Permissible humidity	Up to 95%
Dimensions	65 × 37 × 10 mm
Weight	13 g
Certification	Grade 2, CE
Warranty	<p>Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.</p> <p>Learn more ></p>
Complete set	<p>SpaceControl keyfob</p> <p>CR2032 battery (pre-installed)</p> <p>User's guide</p>