



INC-3URX-256

| Inaxsys Incomlink 3U Rackmount IP Receiver - 256 IP accounts

UNIFY YOUR SECURITY SOLUTION

Incomlink represents the state of art in receivers.

INC-3URX-256 monitoring receiver provides a robust, complete and reliable solution to help build a modern monitoring station.

This device can receive all standard and most non-standard signals from alarm control panels and communicators.

You can have up to 256 accounts without an additional INC-IPLC-2500 IP Line Card.

Features

- ☞ Hardware receiver for both IP and PSTN line cards
- ☞ Functions seamlessly with your automation platform
- ☞ Massive 19" rack housing
- ☞ LCD display with 240x128 pixels
- ☞ Power supply with backup (18Vdc main power / 12Vdc battery)
- ☞ Built in IP card in base configuration (expandable with IP or PSTN cards)
- ☞ 2 serial ports / USB connectors for PC connection
- ☞ 8 additional line card connectors for IP or PSTN expansion (optional)
- ☞ Up to 20,256 total accounts can be monitored per INC-3URX-256 receiver
- ☞ Receiving 4/2, Contact ID and SIA format messages (valid for phone line)
- ☞ IP test code monitoring up to 255 accounts (expandable)
- ☞ Continuous checking of Internet connection
- ☞ Client phone number and IP address display
- ☞ Remote programming (through IP network)
- ☞ Event list monitoring from web browser
- ☞ Encrypted communication (AES-128)
- ☞ Two way radio communication with repeater unit
- ☞ Firmware update function
- ☞ CE declaration, ISO 9001:2009 certificate

Properties

INC-3URX-256	
Power Supply	18Vdc at 2A (main) / 12Vdc at 7Ah (battery)
Maximum current consumption	about 500mA (depends on configuration)
Event buffer	up to 2.000 events
Operating temperature	+10 °C to +30 °C ; 40% relative humidity
Dimension	485 mm x 220 mm x 135 mm
Weight	11.5 lbs

Rear Panel



*Design and specifications are subject to change without notice.