

16-Port PoE Switch w/ 2 Combo Upload ports



Specifications	
Ports	16×100Mbps PoE ports (RJ45), 1×1000Mbps Gigaethernet ports, 1×1000Mbps Combo ports
Standards	IEEE802.3, IEEE802.3u, IEEE802.3z, IEEE802.3ab, IEEE802.3x, IEEE802.3af, IEEE802.3at, IEEE802.3az
Switching capacity	7.2Gbps
Forwarding performance	5.36Mpps
Packet Buffer	4Mbit
MAC	16K
General	
Dimension (H*W*D)	440mm x 189.8mm x 44mm
Weight	2.12KG
Power supply	AC: 100-240V, 50/60Hz
PoE	802.3at/af (4/5+, 7/8-)
Max. PoE Power	Max capacity: 225W Max capacity for single port: 30W
Prior Ports	1~8
Cooling Fans	1
Operating temperature	0°C - 40°C (32°F - 104°F)
Operating humidity	10% - 90% (non condensing)
Storage humidity	5% - 90% (non condensing)
Indicators	
Power	Steady on: AC input is normal Off: No AC input
PoE Indicator	Off: No PoE power supply Steady on: PoE power supply is normal
PoE-Max	Off: The POE power supply power of the whole machine is less than 80% of the specification Steady on: The POE power supply power of the whole machine is greater than 85% of the specification
Link/Act	Off: No link Steady on: Linked Flashing: Transmitting data
Additional Info	
Working Mode	Default(Normal mode) : All ports can communicate with each other. VLAN(Secure mode): Downlink ports can communicate only with uplink ports. Enabling PD keepalive function, the switch will restart the IPC via PoE power when the IPC sends no message in a period of time. Extend(Surveillance mode): Transmission distance up to 250 meters. Downlink ports can communicate only with uplink ports.

*Design and specifications are subjects to change without notice.

