

24-Port PoE Switch w/ 2 Combo Upload ports



Specifications	
Ports	24x100Mbps PoE ports (RJ45), 1x1000Mbps Gigaethernet ports, 1x1000Mbps Combo ports
Standards	IEEE802.3, IEEE802.3u, IEEE802.3z, IEEE802.3ab, IEEE802.3x, IEEE802.3af, IEEE802.3at, IEEE802.3az
Switching capacity	8.8Gbps
Forwarding performance	6.55Mpps
Packet Buffer	4Mbit
MAC	16K
General	
Dimension (H*W*D)	440mm x 244.8mm x 44mm
Weight	2.93KG
Power supply	AC: 100-240V, 50/60Hz
PoE	802.3at/af (4/5+, 7/8-)
Max. PoE Power	Max capacity: 370W Max capacity for single port: 30W
Prior Ports	1~8
Cooling Fans	1
Operating temperature	0°C - 40°C (32°F - 104°F)
Operating humidity	10% - 90% (non condensing)
Storage humidity	5% - 90% (non condensing)
Indicators	
Power	Steady on: AC input is normal Off: No AC input
PoE Indicator	Off: No PoE power supply Steady on: PoE power supply is normal
PoE-Max	Off: The POE power supply power of the whole machine is less than 80% of the specification Steady on: The POE power supply power of the whole machine is greater than 85% of the specification
Link/Act	Off: No link Steady on: Linked Flashing: Transmitting data
Additional Info	
Working Mode	Default(Normal mode) : All ports can communicate with each other. VLAN(Secure mode): Downlink ports can communicate only with uplink ports. Enabling PD keepalive function, the switch will restart the IPC via PoE power when the IPC sends no message in a period of time. Extend(Surveillance mode): Transmission distance up to 250 meters. Downlink ports can communicate only with uplink ports.

*Design and specifications are subjects to change without notice.