

INSBO4KIRF

8MP IR Fixed-focal Bullet Network Camera

- 8MP 1/2.7" CMOS image sensor, HD image
- WDR (120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in IR LED, max IR distance: 30 m (98.43 ft)
- Intelligent detection: Intrusion, tripwire
- Abnormality detection: Motion detection, audio detection

Unify your Security Solution

This camera offers vivid imaging in any scenario. Using industry-leading WDR technology, you'll be able to capture the subject in the most difficult lighting conditions.

Smart H.265+ & H.264+

STORM smart encoding technology can provide high-quality video with higher efficiency and can also reduce the cost of storage space and transmission adopting an advanced algorithm of auto stream control.

On-board Analytics

This camera responds accurately to specific events in a given area. Our algorithm enables Tripwire violations, intrusion detection, abandoned/missing objects and much more. Facilitate your viewing experience using on the edge analytics – one product, multiple features.



*Design and specifications are subjects to change without notice.



INSBO4KIRF

8MP IR Fixed-focal Bullet Network Camera

Product Specifications

Camera					
Image Sensor	1/2.7" 8 Megapixel progressive CMOS				
Effective Pixels	3840(H) x 2160(V)				
RAM/ROM	256MB/128MB				
Scanning System	Progressive				
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s				
Minimum Illumination	0.009 Lux at F2.0 (Color, 30 IRE) 0.0009 Lux at F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)				
S/N Ratio	More than 56 dB				
IR Distance	30 m (98.43 ft)				
IR LEDs	1				
Camera Features					
Day/Night	Auto(ICR) / Color / B/W				
Backlight Compensation	BLC / HLC / WDR (120dB)				
White Balance	Auto / natural / street lamp / outdoor / manual / regional custom				
Gain Control	Auto/Manual				
Noise Reduction	3D DNR				
Motion Detection	OFF/ON (4 areas, rectangular)				
Region of Interest	Yes (4 areas)				
Smart Illumination	Supported				
Mirror	Yes				
Privacy Masking	4 Areas				
Lens					
Lens Type	Fixed Lens				
Mount Type	Board-in				
Focal Length	2.8mm				
Max. Aperture	F2.0				
Close Focus Distance	1.3 m (4.27 ft)				
Viewing Angle	Horizontal: 106.0° Vertical: 56.0° Diagonal: 125.0°				
Pan/Tilt/Rotation	Pan: 0°–360°; Tilt: 0°–90°; D: 0°–360°				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8mm	88.0 m (288.71 ft)	35.2 m (115.49 ft)	17.6 m (57.74 ft)	8.8 m (28.87 ft)
Video					
Compression	H.265+; H.264+; H.265; H.264; MJPEG				
Resolution	4K (3840×2160) / 6M (3072×2048) / 5M (2560×1920) / 3M (2048×1536) / 3M (2304×1296) / 1080P (1920×1080) / 1.3M (1280×960) / 720P (1280×720) / D1 (704×576/704×480) / VGA (640×480) / CIF (352×288/352×240)				
Frame Rate	Main Stream: 3840 × 2160 (1 fps to 25/30 fps); 2688 × 1520 (1 fps to 25/30 fps) Sub stream: 704 × 576 at (1 fps to 25 fps); 704 × 480 at (1 fps to 30 fps)				
Bit Rate	H.264: 32Kbps - 8192Kbps H.265: 16Kbps - 8192Kbps				

*Design and specifications are subjects to change without notice.



INSBO4KIRF

8MP IR Fixed-focal Bullet Network Camera

Product Specifications

Intelligent Functions	
Event Trigger	Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos
Smart Functions	Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
Network	
Ethernet	RJ-45 (10/100 Base-T)
Storage	FTP; SFTP; Micro SD card (support max. 256 GB); NAS
SDK and API	Yes
Management Software	STORM, STORM+, ARKIV
Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; Bonjour
Cyber Security	Configuration encryption; trusted execution; Digest; security logs; WSSE; account lockout; syslog; video encryption; 802.1x; IP/MAC filtering; HTTPS; trusted upgrade; trusted boot; firmware encryption; generation and importing of X.509 certification
Compatibility	ONVIF (Profile S/Profile G/Profile T); CGI; P2P; Milestone
Video Management Software	STORM; STORM+; ARKIV
Maximum User Access	20
Smart Phone	iOS, Android
Certification	
Certifications	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; FCC: 47 CFR FCC Part 15, Subpart B; UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07
General	
Power Supply	12 VDC/PoE (802.3af)
Power Consumption	Basic: 2.7 W (12 VDC); 3.4 W (PoE) Max. (H.265 + max. resolution + max. stream + WDR + IR intensity + AI): 4.5 W (12 VDC); 5.4 W (PoE)
Working Environment	-40°C to +60°C (-40°F to +140°F); Less than 95% RH
Protection	IP67
Dimensions	166.2 mm × 70 mm × 70 mm (6.54" × 2.76" × 2.76")
Weight	1.06 lbs (0.48kg)


*Design and specifications are subjects to change without notice.



INSBO4KIRF

8MP IR Fixed-focal Bullet Network Camera

Product Specifications



**INSX134
Junction Box**




**INSX130
Junction Box**



**INSX152
Pole Mount**



**VUSD256G
Micro SD Card**



*Design and specifications are subjects to change without notice.

