

INSBO6180IRF

3x2MP (6MP) H265 Network Multi-Lens IR Panoramic Bullet W/IR W/SD Slot

- Three 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS
- Wide Dynamic Range 120dB
- H.265 & H.264 dual-stream encoding
- Built-in IR LED, max IR distance: 30 m
- Intelligent detection: Intrusion, tripwire, heatmap
- Micro SD card up to 128 GB



Unify your Security Solution

Starlight Technology Improve your levels of security by using our Starlight technology. With its optical features, Starlight Technology will be able to balance all lighting throughout a scene. This will capture any colored details regardless of the lighting.

Wide Dynamic Range

Our camera offers TRUE WDR technology produce a high-quality picture across a wide range of lighting levels

On-board Analytics

This camera responds accurately to specific events in a given area. Our algorithm enables Tripwire violations, intrusion detection, abandoned/missing objects and much more. Facilitate your viewing experience using on the edge analytics – one product, multiple features.



*Design and specifications are subjects to change without notice.



INSBO6180IRF

3x2MP (6MP) H265 Network Multi-Lens
IR Panoramic Bullet W/IR W/SD Slot

Product Specifications

Camera					
Image Sensor	Three 1/2.8" 2Megapixel progressive scan CMOS				
Effective Pixels	4096(H) x 832(V)				
RAM/ROM	1024MB / 128MB				
Scanning System	Progressive				
Electronic Shutter Speed	Auto/Manual, 1/3~1/100,000s				
Minimum Illumination	0.007 Lux / F1.8 (Color, 1/3s, 30IRE); 0.05 Lux / F1.8 (Color, 1/30s, 30IRE); 0 Lux / F1.8 (IR on)				
S/N Ratio	More than 50dB				
IR Distance	Distance up to 30m(98ft)				
IR LEDs	8				
Camera Features					
Day/Night	Auto(ICR) / Color / B/W				
Blacklight Compensation	BLC / HLC / WDR(120dB)				
White Balance	Auto / Natural / Street Lamp / Outdoor / Manual				
Gain Control	Auto/Manual				
Noise Reduction	3D DNR				
Digital Zoom	16x				
Privacy Masking	4 Areas				
Lens					
Lens Type	Fixed				
Mount Type	Board-in				
Focal Length	3.6mm				
Max. Aperture	F1.8				
Viewing Angle	H: 180°, V:44°				
Optical Zoom	N/A				
Focus Control	Fixed				
Pan/Tilt/Rotation	Pan: 0°~360°; Tilt: 0°~90°; Rotation: 0°~360°				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	3.6 mm	52m(171ft)	21m(69ft)	10m(33ft)	5m(16ft)
Video					
Compression	H.265+ / H.265 / H.264+ / H.264				
Resolution	4096x832 / 3840x780 / 2560x520 / 1280x260 / 1024X208				
Frame Rate	Main Stream: 4096x832 (1 to 25/30fps)				
	Sub Stream: 1024x208 (1 to 25/30fps)				
	Third Stream: 1280x260 (1 to 25/30fps)				
Bit Rate	H.265: 4Kbps ~ 10Mbps; H.264: 8Kbps ~ 16Mbps				
Audio					
Compression	G.711a / G.711Mu / AAC / G.726				

*Design and specifications are subjects to change without notice.



INSBO6180IRF

3x2MP (6MP) H265 Network Multi-Lens
IR Panoramic Bullet W/IR W/SD Slot

Product Specifications

Smart Functions	
Intelligent Functions	Tripwire, Intrusion, Object Abandoned/Missing
Smart Features	Heatmap, E-PTZ
Network	
Ethernet	RJ-45 (100/1000Base-T)
Protocol	HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP
Compatibility	PSIA, CGI
Maximum User Access	10 Users/20 Users
Management Software	STORM, STORM+, ARKIV
Edge Storage	NAS; Micro SD card up to 128GB
Smart Phone	iOS, Android
Interface	
Video Interface	1 Port(For adjustment only)
Audio Interface	1/1 channel In/Out
RS485	N/A
Alarm	2 channel In: 5mA 5VDC 1 channel Out: 1A 30VDC / 0.5A 50VAC
General	
Power Supply	AC24V, PoE+ (802.3at)(Class 4)
Power Consumption	Less than 23W
Working Environment	-40° C ~ +60° C (-40° F ~ +140° F) / Less than 95% RH
Ingress Protection	IP67
Vandal Protection	IK10
Dimensions	298.3mm×172.5mm×120.5mm (11.74"×6.79"×4.74")
Weight	7.52 lbs (3.41 kg)



*Design and specifications are subjects to change without notice.



INSB06180IRF

3x2MP (6MP) H265 Network Multi-Lens
IR Panoramic Bullet W/IR W/SD Slot

Product Specifications



**INSX120
Junction Box**






**INSX151
Wall Mount**



**INSX150
Pole Mount**



**VUSD128G
Micro SD Card**

Wall Mount	Pole Mount
INSX120	INSX120 + INSX150
	
Corner Mount	
INSX120 + INSX151	
	

*Design and specifications are subjects to change without notice.

