


INSDNVD

Ultra-HD Network Video Decoder

- 2ch at 8K / 10ch at 4K / and more real-time decoding ability
- HDMI input max support 1 channel 4K at 60fps
- 4ch HDMI output max support 4K at 60fps output
- Up to 8K image splicing display
- Supports up to 4 video-wall display units or monitors
- Supports 1 / 4 / 6 / 8 / 9 / 16 / 25 / 36 and free split
- Supports alarm, RS232, RS485
- Splicing screens control for zoom / merge / roam / overlay



*Design and specifications are subjects to change without notice.



INSDNVD

Product Specifications

Ultra-HD Network Video Decoder

System	
Main Processor	Embedded processor
Operating System	LINUX
Performance	
Video Format	H.265+ / H.265 / H.264 / MJPEG / MPEG2 / MPEG4
Audio Format	PCM / G.711 / AAC
Total Video Decoding	2-channel 32MP at 25/7-ch; 12MP at 25/10-ch; 8MP at 25/14-ch 6MP at 25/36-ch; 1080P at 30/144-ch; D1 at 30
Decoding Resolution	32MP / 12MP / 8MP / 6MP / 5MP / 3MP / 1080P / 720P / 960H / D1 / HD1 / 2CIF / CIF / QCIF
Video Frame Rate	PAL:1-25fps ,NTSC:1-30fps
Human Body	Top, top color, bottom, bottom color, hat, bag, gender, age, umbrella.
Video Input	1-ch at HDMI 2.0, 1-ch at HDMI 1.4
Video Output	4-ch at HDMI 2.0
Collection Resolution	3840x2160 at 60fps / 3840x2160 at 30fps; 1920x1080 at 60fps; 1680x1050 / 1440x900 / 1280x1024 / 1280x960 / 1280x800 / 1280x720 / 1024x768 / 800x600
Display Resolution	4096x2160 at 24fps; 3840x2160 at 60fps / 3840x2160 at 30fps; 1920x1080 at 60fps; 1280x1024 / 1280x720 / 1024x768
Bi-directional Talk	1 Pair 3.5mm jack (reserved) (2.0V Line in/50mV Mic in/10KΩ, 2.0V/16Ω out)
Audio Output	1 x 3.5mm jack
Alarm Input	8ch
Alarm Output	8ch
Communication Interface	1 x RJ45 network port (10M/100M/1000M); 2 x RS232; 1 x RS485
General	
Power Supply	DC12V, 5A
Power Consumption	Less than 60W
Working Temperature	10 °C to +55 °C (14 °F to 131 °F)
Working Humidity	10% ~ 95%, 86Kpa ~ 106Kpa
Unit Dimension	1U, 440 × 322.25 × 44mm (17.32 × 12.69 × 1.73 inch), (W*D*H)
Weight	3.5 kg

*Design and specifications are subjects to change without notice.

