

# INSD08360IRWA

## 4x2MP (8MP) H265 Network Multi-Lens IR Dome W/SD Slot

- Four 1/2.8" 2 Megapixel progressive scan STARVIS™ CMOS
- True wide dynamic range 140dB
- H.265+ & H.264+ dual-stream encoding
- Built-in IR LED, max IR distance: 30 m
- Intelligent detection: Intrusion, tripwire
- Micro SD card up to 256 GB

### Unify your Security Solution

Starlight Technology Improve your levels of security by using our Starlight technology. With its optical features, Starlight Technology will be able to balance all lighting throughout a scene. This will capture any colored details regardless of the lighting.

### Smart H.265+ & H.264+

STORM smart encoding technology can provide high-quality video with higher efficiency and can also reduce the cost of storage space and transmission adopting an advanced algorithm of auto stream control.

### On-board Analytics

This camera responds accurately to specific events in a given area. Our algorithm enables Tripwire violations, intrusion detection, abandoned/missing objects and much more. Facilitate your viewing experience using on the edge analytics – one product, multiple features.



\*Design and specifications are subjects to change without notice.

# INSD08360IRWA

4x2MP (8MP) H265 Network  
Multi-Lens IR Dome W/SD Slot

## Product Specifications

Camera					
Image Sensor	Four 1/2.8" 2 Megapixel progressive scan CMOS				
Effective Pixels	1920(H) x 1080(V)				
RAM/ROM	1024MB / 128MB				
Scanning System	Progressive				
Electronic Shutter Speed	Auto/Manual, 1/3(4)~1/100,000s				
Minimum Illumination	0.005 Lux / F1.8 (Color, 1/3s, 30IRE); 0.06 Lux / F1.8 (Color, 1/30s, 30IRE); 0 Lux / F1.8 (IR on)				
S/N Ratio	More than 50dB				
IR Distance	Distance up to 30m (98ft)				
IR LEDs	8				
Camera Features					
Day/Night	Auto(ICR) / Color / B/W				
Backlight Compensation	BLC / HLC / WDR(140dB)				
White Balance	Auto/Manual				
Gain Control	Auto/Manual				
Noise Reduction	3D DNR				
Digital Zoom	16x				
Privacy Masking	4 Areas				
Lens					
Lens Type	Motorized				
Mount Type	Board-in				
Focal Length	2.7mm - 12mm				
Max. Aperture	F1.8				
Viewing Angle	H: 105° ~ 44°, V:54° ~ 25°				
Optical Zoom	4x				
Focus Control	Motorized				
Pan/Tilt/Rotation	Pan: 0° ~ 360°; Tilt: 0° ~ 80°; Rotation: 0° ~ 355°				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	W	45m(148ft)	18m(59ft)	9m(29.5ft)	4.5m(14.8ft)
	T	99m(325ft)	40m(131ft)	20m(66ft)	10m(33ft)
Video					
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG(sub stream)				
Resolution	1080P (1920x1080) / 1.3M (1280x960) / 720P (1280x720) / D1 (704x576/704x480) / VGA (640x480) / CIF (352x288/352x240)				
Frame Rate	Main Stream: 1080P (1 to 25/30fps)				
	Sub Stream: D1 (1 to 25/30fps)				
Bit Rate	H.264: 32~8192Kbps; H.265: 12~6144Kbps				
Audio					
Compression	G.711a / G.711Mu / AAC / G.726				

\*Design and specifications are subjects to change without notice.



# INSD08360IRWA

4x2MP (8MP) H265 Network  
Multi-Lens IR Dome W/SD Slot

## Product Specifications

Smart Functions	
Intelligent Functions	Tripwire, Intrusion
Event Trigger	Motion detection, Video tampering, Scene changing, Network disconnection, Ip address conflict, Illegal access, Storage anomaly
Network	
Ethernet	RJ-45 (100/1000Base-T)
Protocol	HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP; QoS; UPnP; NTP
Storage	NAS; Micro SD Card up to 256GB
Video Management Software	STORM, STORM+, ARKIV
Compatibility	ONVIF Profile S&G, API
Maximum User Access	10 Users / 20 Users
Smart Phone	iOS, Android
Interface	
Video Interface	N/A
Audio Interface	1/1 channel In/Out
RS485	1 port
Alarm	1 channel In: 5mA 5VDC 1 channel Out: 300mA 12V
General	
Power Supply	AC24V, PoE(802.3at) (Class 4)
Power Consumption	AC 24V: 9.9W to 31.2W (IR on) PoE: 10.6W to 23.8W (IR on)
Working Environment	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Ingress Protection	IP67
Vandal Protection	IK10
Dimensions	286.1mm × 111.3mm
Weight	7.94 lbs (3.6kg)


\*Design and specifications are subjects to change without notice.



# INSD08360IRWA

4x2MP (8MP) H265 Network  
Multi-Lens IR Dome W/SD Slot

## Product Specifications



**INSX303  
Wall Mount**



**INSX111  
Mount Adapter**



**INSX108  
Mount Adapter**



**INSX300  
Ceiling Mount**

Ceiling Mount	Wall Mount
INSX111 + INSX300 + INSX108	INSX111 + INSX303 + INSX108



**VUSD128G  
Micro SD Card**

\*Design and specifications are subjects to change without notice.

